


MIRAI
by chimei

22
56cm

DTL-722P302
LCD TV



WWW.MIRAI.EU



...experience the future

Jupiterstraat 82 • 2132 HE Hoofddorp • The Netherlands
Email: info@chimei.eu • Tel: +31 (0)23 - 565 6930 • Fax: +31 (0)23 - 565 6931
www.mirai.eu

22 DTL-722P302

56cm LCD TV

Screen Size	473.76(H) x 296.1(V)
Aspect Ratio	16 : 10
Pixel Pitch	0.282 (H) x 0.282 (V)mm
Panel Resolution	1680 x 1050
Brightness	300 cd/m2
Contrast Ratio (typ.)	700 : 1 (2800 : 1 Dynamic)
Response Time (typ.)	5 ms
Viewing Angles (typ.)	170°(H) / 160°(V)
Standard TV	B/G, D/K, I, L/L=
Tuner System	PAL, SECAM, NTSC Video
Display Color	16.7 M
Control Panel	Power (On/Off), Source Select (SCART 1/SCART 2/YPbPr/VGA/HDMI/TV), TV/DTV), Menu(OSD) Operation, Channel Up, Channel Down, Volume +, Volume -, IR Receiver
Terminal I/O	Full SCART - SCART 1: S-RGB/AV(IN), TV(OUT) VGA Input (YPbPr via VGA connector), PC Audio In (for VGA), HDMI, Headphone Output
Support Timing	480i, 480p, 576i, 576p, (HDTV) 720p, 1080i, (DTV) integrated DVB-T
Speaker	3W x 2
User Controls	Contrast, Brightness, Back Light, Saturation, Colour Temp, Red, Green, Blue, White Balance, Picture Mode, DCI, LTI, Auto (picture setup), Clock, Phase, H-Position, V-Position, CH Scan, Program, Manual Scan, Update Scan, Audio (Balance, Bass, Treble), Language
Pic-Mode	Movie/ Game/ Sport/ Vivid/ User
Sleep Timer Function	Off / 15 min. / 30 min. / 60 min. / 90 min. / 120 min.
Teletext	250 pages
Power Supply	AC 100-240 V, 1.5A, 50/60Hz
Power Consumption	Operation < 60W, Standby < 2W
Safety / EMC	CB, Intertek-GS, CE, RoHS, WEEE
Accessories	Remote Control, Batteries, User Manual, Power Cord, Power Adapter
VESA mounting	100 x 100 mm
System Dimension	539.7(W) x 437.2(H) x 182(T) mm
Carton Size	580(W) x 500(H) x 122(T) mm
N.W./G.W.	5.9 kg/ 7.2 kg



...experience the future